



Z.I. de Boisse
 9, rue Montgolfier
 F-87203 SAINT JUNIEN Cedex
 FRANCE
 Tél. : +33 (0) 555 02 26 32
 Fax : +33 (0) 555 02 55 25
 E-mail : snfbo@snfbo.com
www.snfbo.com



VEBEO FITTINGS ISO 1179-2




- ✓ ISO 1179-2
- ✓ ISO 1179-1 (threaded ports)
- ✓ ISO 9227 (Zn Ni)

Advantages of FBO 1179 Fittings

- Fit Form function, Interchangeability
- Low temp and Very low Temp
- Harsh environment
- BS / Salt Spray 960 Hours
- Surface Treatment or Stainless Steel

UISOM




For ordering : the fitting with the order code 020219-A34-1271 is also defined by the description number : UISOMAZN_INBT_BSK_12_G1/8ACYL

thread BSPP G1/8A
 tube Ø12mm
 groove split tapered ring
 + washer 304L stainless steel
 NBR BT O-ring -45°C
 Zinc Nickel coated steel
 Parallel male union ISO 1179-2

Tube OD	Thread Ød ₁	Ød ₃ L series	s ₁ hex	s ₂ hex	L	LT	L ₁	Weight (gr)	Order Code
12	G1/8	4	22	24	32,5	19	8	60	020219-A34-1271
12	G1/4	6	19	24	35,5	19	12	62	020219-A34-1272
12	G3/8	9	22	24	37,5	19	12	72	020219-A34-1273
18	G3/8	9	27	30	40,5	22	12	104	020219-A34-1873
18	G1/2	14	27	30	43	22	14	119	020219-A34-1874
28	G1/2	14	41	46	46,5	24	14	249	020219-A34-2874
28	G3/4	18	41	46	48,5	24	16	262	020219-A34-2875
28	G1"	23	41	46	50,5	24	18	282	020219-A34-2876
35	G3/4	18	46	50	54	29	16	321	020219-A34-3575
35	G1"	23	46	50	56	29	18	340	020219-A34-3576
35	G1"1/4	30	50	50	59	29	20	414	020219-A34-3577
35	G1"1/2	30	55	50	61	29	22	547	020219-A34-3578

AISOM



For ordering : the fitting with the order code 020619-A09-1271 is also defined by the description number : AISOMAZN_INBT_12_G1/8ACYL

Thread BSPP G1/8
 Adaptor Ø12mm
 NBR BT O-ring -45°C
 Zinc Nickel coated steel
 Parallel male stem adaptor ISO 1179-

Tube OD	Thread Ød ₁	Ød ₃ L series	s ₁ hex	LA	L	L ₁	Weight (gr)	Order Code
12	G1/8	4	14	20	35	8	27	020619-A09-1271
12	G1/4	6	19	20	39,5	12	37	020619-A09-1272
12	G3/8	9	22	20	41,5	12	45	020619-A09-1273
18	G3/8	9	22	24	45,5	12	73	020619-A09-1873
18	G1/2	14	27	24	48	14	70	020619-A09-1874
28	G1/2	14	30	30	56	14	178	020619-A09-2874
28	G3/4	18	32	30	58	16	172	020619-A09-2875
28	G1"	23	41	30	61	18	197	020619-A09-2876
35	G3/4	18	36	34	62	16	292	020619-A09-3575
35	G1"	23	41	34	65	18	296	020619-A09-3576
35	G1"1/4	30	50	34	69	20	321	020619-A09-3577
35	G1"1/2	30	55	34	71	22	454	020619-A09-3578

The above listed order codes are for standard fittings. Other materials, sizes and equipment can be produced on request.